

## SATISFACTION GUARANTEED

We are sure that Cannondale bicycles are the finest bicycles in the world. That's why we confidently offer the best guarantee in the industry. Cannondale bicycles, like all Cannondale products, are covered with our 100% guarantee of satisfaction. If you are ever dissatisfied with your Cannondale bicycle, we will repair or replace it free of charge. We also offer an exclusive frame replacement policy. If you damage your Cannondale frame, we will send you a new one for just \$150 and the return of your damaged frame. (\$200 for *Alumina Classic* Frame replacement.)

## CALL OUR TOLL-FREE HOTLINE: 1 800 BIKE USA

Communication with our customers has always been the most important component in Cannondale's customer service. Our toll-free phone number is your direct line to Cannondale. Give us a call to find the location of your local authorized Cannondale bicycle dealer, or if you have questions or comments about Cannondale bicycles or any Cannondale product. (In Connecticut or outside the continental USA, please call 1 (203) 838-4488.)

Prices, specifications and colors are subject to change without notice. If the proposed tariff bill (H.R. 2226) is passed there will be an increase in the cost of components and subsequently an increase in the retail prices of bicycles.  
©1985 Cannondale Corporation, 9 Brookside Place, Georgetown, CT 06829

## CANNONDALE FRAMESETS

All Cannondale models are available as framesets as well as complete bicycles. Cannondale framesets come with headset, fork, front derailleur, and color accessory package which includes saddle, cable housings, handlebar tape and brake hoods.

### FRAME SPECIFICATIONS: *Racing*\*

Size	48	50	53	54.5	56
Seat Tube Angle	77°	75.7°	74.4°	74°	73.7°
Head Tube Angle	72°	72.8°	73°	73°	73°
Top Tube Length	20.1	21.1	21.8	21.9	22
Chainstay Length	15.75	15.75	15.75	15.75	15.75
Fork Rake	1.75	1.625	1.5	1.5	1.5
Bottom Bracket Height	10.75	10.75	10.75	10.75	10.75
Wheelbase	38.8	38.9	38.9	38.9	38.9
Trail	2.5	2.5	2.5	2.5	2.5
Ground to Top of Top Tube	28.3	29.6	30.6	31.3	31.9