

ALUMINA CLASSIC FRAMESETS

New this year from Cannondale is the *Alumina Classic* series of specially hand-finished framesets that have the elegant appearance of a custom built bicycle. Look for the *Alumina Classic* Frame on the SR1000, SR900, SR800, and ST800 model bicycles. These bicycles and framesets will only be available in limited quantities in 1986.

THE FINEST COMPONENTS

We're proud of Cannondale bicycle frames, so we won't put just any components on them. We select each component package carefully to complement the bicycle's intended use, always maintaining our high standards of function, durability, style and value.

<i>Touring</i>			<i>All-Terrain</i>				<i>Town and Country</i>								
58	60	63	19	21	23	25	27	16	18†	20†	22†	16	18	20	22
73.1°	73°	73°	76.7°	73.5°	73.5°	73.5°	73.5°	73.5°	73.5°	73.5°	73.5°	73.5°	73.5°	73.5°	73.5°
73°	73°	73.5°	72°	72°	72°	72°	72°	68°	69.5°	69.5°	69.5°	71°	71°	71°	71°
22.1	22.3	23.1	20.3	21.75	22.25	23.25	24.25	21.5	22.5	23.25	24.25	20	21.5	22.25	23.25
15.75	15.75	15.75	18	18	18	18	18	17.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5
1.5	1.5	1.38	2.125	2.125	2.125	2.125	2.125	1.75	1.75	1.75	1.75	2	2	2	2
10.75	10.75	10.75	10.2	10.3	10.44	10.52	10.63	12.75	13	13	13	10.63	10.63	10.63	10.63
38.8	39	39.5	41.1	41.3	41.6	42.7	44	42.8	43.2	44.1	45.2	40.9	41.9	42.8	43.9
2.5	2.5	2.5	2.15	2.15	2.15	2.15	2.15	3	3	3	3	2.36	2.36	2.36	2.36
32.6	33.2	34.5	28.5	30.5	32.5	34.5	36.5	27.1‡	29.2‡	31.1‡	32.9‡	27.3	28.7	30.7	32.7

*Size of racing bicycles measured in cm.

† For dual 26 inch wheels. Specifications will be identical for the SM700 with the 24" rear wheel, but subtract an inch from the chainstays and wheelbase.

‡ Effective height. Actual height would be lower due to sloping top tube.

All Cannondale bicycles are equipped to meet CPSC regulations. Ride smart, always wear a helmet.